

- Recessed gimble ideal for highlighting area and items of interest, such as pictures and ornaments.



FEATURES

- Die-cast aluminium heat sink
- High efficiency SMD chips
- Constant current driver
- 40 degree gimble angle
- Opal polycarbonate diffuser
- CA90 rated

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

INCLUDES

- Gimble LED downlight
- Dimmable LED driver
- 1.2 m flex and plug

APPLICATIONS

- Residential
- Hotels
- Shops
- Conference rooms
- Reception areas

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION			IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)
					 Ra≥80		

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Net Weight (kg)
172007A	220-240V	11W	0.9	3000K	800lm	100°	35000h	0.37
172008A	220-240V	11W	0.9	4000K	850lm	100°	35000h	0.37
172077A	220-240V	11W	0.9	5000K	850lm	100°	35000h	0.37

Part No.	Model No.	Driver Model No.	VEET Status	IPART Status
172007A	YKRS3EA2G1W-D-11W	YKD12CC270D	Approved No.: 5463	Approved No.: 24143D12-1HJDGHF
172008A	YKRS3EA2G1W-D-11W	YKD12CC270D	Approved No.: 5463	Approved No.: 24143D12-1HJDGHF
172077A	YKRS3EA2G1W-D-11W	YKD12CC270D	Approved No.: 5463	Approved No.: 24143D12-1HJDGHF

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 C~+40 C

