

- Corrosion proof, good vandal resistance for general circulation areas.



FEATURES

- Polycarbonate body and diffuser
- Built-in high efficiency SMD chips
- Constant current driver fitted
- IP65 weatherproof and IK10 vandal-proof
- Sustained emergency system
- Large 6mm terminal block for easy installation
- Fully approved to AS2293 standards
- Emergency classification: C₀: D32, C₉₀: D32
- Fitting colour: White

INCLUDES

- LED bunker with driver
- Mounting accessories
- Emergency system (driver, LED and battery)

INSTALLATION OPTIONS

- Surface mounted

APPLICATIONS

- Walkways
- Hallways
- Balconies
- Industrial
- Commercial

WARRANTY

- Five years for fitting
- One year for battery

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING

Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Net Weight (kg)
282004EM	YKBHEB1-EC-13W	100-240V	13W	0.9	3000K	1100lm	110°	50000h	1.50
282005EM	YKBHEB1-EC-13W	100-240V	13W	0.9	4000K	1200lm	110°	50000h	1.50
282006EM	YKBHEB1-EC-13W	100-240V	13W	0.9	5000K	1200lm	110°	50000h	1.50

Part No. of Battery	Battery Capacity	Battery Voltage	Battery Type
173010	5000mAh	3.6V	Li(NiCoMn)O2

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:0 °C ~ +40 °C

