



FEATURES

- Die-cast housing
- High efficiency COB LED chips
- Optical reflector
- Integrated LED driver

INCLUDES

- Constant current LED driver
- Bracket and terminal block
- Fixing screws

INSTALLATION OPTIONS

- Surface mount

APPLICATIONS

- Residential
- Decorative
- Commercial

WARRANTY

- Three years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)
		Non dim	Ra≥80		

Part No.	Order Code	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Fitting Colour	Net Weight (kg)
173273	173273	RSD09D1-C-A 10W	220-240V	10W	0.9	3000K	760lm	60°	35000h	Black	0.50kg
173274	173274	RSD09D1-C-A 10W	220-240V	10W	0.9	4000K	820lm	60°	35000h	Black	0.50kg
173275	173275	RSD09D1-C-A 10W	220-240V	10W	0.9	5000K	820lm	60°	35000h	Black	0.50kg
173283	173283	RSD09D1-C-A 10WWH	220-240V	10W	0.9	3000K	760lm	60°	35000h	White	0.50kg
173284	173284	RSD09D1-C-A 10WWH	220-240V	10W	0.9	4000K	820lm	60°	35000h	White	0.50kg
173285	173285	RSD09D1-C-A 10WWH	220-240V	10W	0.9	5000K	820lm	60°	35000h	White	0.50kg

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+50 °C

