

- Replacement For Traditional MR16/GU10 50W



Module & driver



Lamp holder

FEATURES

- Plastic downlight module with internal aluminium heat sink
- High efficiency SMD chips
- Constant current driver
- Optical design of the lens
- To suit downlight holder

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

INCLUDES

- LED downlight
- Dimmable LED driver
- 1.0 m flex and plug

APPLICATIONS

- Residential
- Hotels
- Shops
- Conference rooms
- Reception areas
- Bathrooms and wet areas

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)
		leading and trailing edge	Ra≥80		

Module and Driver

Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Net Weight (kg)
263003	RS2A1-WDT-MA 6W	220-240V	6W	0.9	3000K	550lm	60°	35000h	0.16
263004	RS2A1-WDT-MA 6W	220-240V	6W	0.9	4000K	600lm	60°	35000h	0.16

Downlight Holder

Part No.	Model No.	Cutout (mm)	Fitting Colour	Housing Material	Remarks
292001	ECA5RS	68-72	White	Die-cast Metal	Fixed Head

[1] Operating Frequency=50/60Hz; [2] Operating Temperature:-20 °C~+45 °C; [3] IP54 Only for module

*Note - Order module and driver plus downlight holder for complete luminaire.

