energetic®
Smarter lighting

SupValue Mini Globe

LED Fancy Round Lamps

• Designed for domestic use in smaller fittings.

FEATURES

- High lumen output efficiency
- Long lifetime 15000hrs
- Edison screw and bayonet cap available
- Low surface temperature for extra safety

DIMMING OPTIONS

- Trailing and leading edge
- Universal

APPLICATIONS

- Residential
- Retail
- Cafes
- Restaurants
- Display areas
- Atriums and heritage applications

WARRANTY

- Three years (subject to terms and conditions)

Lamps

CERTIFICATION	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)
	leading and trailing edge	Ra≥80		Ø45 87 E14; Ø45 85 B15; Ø45 84 E27; Ø45 82 B22

Order Code	Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Cap	Lumens	Beam Angle	Lifetime L70B50
132109C	132109F	YKG45C9-D-6W	220-240V	6W	0.8	3000K	E14	470lm	225°	15000h
132110C	132110F	YKG45C9-D-6W(B15)	220-240V	6W	0.8	3000K	B15	470lm	225°	15000h
132111C	132111F	YKG45C9-D-6W(E27)	220-240V	6W	0.8	3000K	E27	470lm	225°	15000h
132112C	132112F	YKG45C9-D-6W(B22)	220-240V	6W	0.8	3000K	B22	470lm	225°	15000h
132113C	132113F	YKG45C9-D-6W	220-240V	6W	0.8	4000K	E14	500lm	225°	15000h
132114C	132114F	YKG45C9-D-6W(B15)	220-240V	6W	0.8	4000K	B15	500lm	225°	15000h
132115C	132115F	YKG45C9-D-6W(E27)	220-240V	6W	0.8	4000K	E27	500lm	225°	15000h
132116C	132116F	YKG45C9-D-6W(B22)	220-240V	6W	0.8	4000K	B22	500lm	225°	15000h
132117C	132117F	YKG45C9-D-6W	220-240V	6W	0.8	6500K	E14	500lm	225°	15000h
132118C	132118F	YKG45C9-D-6W(B15)	220-240V	6W	0.8	6500K	B15	500lm	225°	15000h
132119C	132119F	YKG45C9-D-6W(E27)	220-240V	6W	0.8	6500K	E27	500lm	225°	15000h
132120C	132120F	YKG45C9-D-6W(B22)	220-240V	6W	0.8	6500K	B22	500lm	225°	15000h

[1] Operating Frequency=50/60Hz;
[2] Operating Temperature:-20℃~+45℃

Specifications are for reference only and may be changed without prior notification.
Version: V6.0