

- For use in existing CFL downlights with two pins.



FEATURES

- Energy efficient alternative to fluorescent tubes
- High efficient SMD chips
- Fully integrated driver
- Opal polycarbonate diffuser
- Low surface temperature for extra safety
- Rotatable end cap

APPLICATIONS

- Residential
- Retail
- Cafes
- Restaurants
- Display areas
- Atriums and heritage applications

WARRANTY

- Three years (subject to terms and conditions)

CERTIFICATION	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)
	 Non dim	 Ra≥80		

Part No.	Voltage	Watt.	PF	Color Temp.	Cap	Lumens	Beam Angle	Lifetime L70B50
162008	220-240V	8W	0.9	4000K	G24d(+60°)	675lm	130°	25000h
162015	220-240V	12W	0.9	4000K	G24d(+120°)	1350lm	130°	25000h

Part No.	Model No.	VEET Status	IPART Status
162008	YKPLCC1-8W	Approved No.: 4316	Approved No.: 24143S10-6EEFBHH
162015	YKPLCC1-12W	Approved No.: 4316	Approved No.: 24143S10-6EEFBHH

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+45 °C

*Some luminaires may need to be rewired for the lamps to operate.

Please follow instructions supplied with product.

