



- Ideal for replacement of existing 6 inch and 8 inch luminaires.



Adapter plate

FEATURES

- Die-cast aluminium heat sink
- High efficiency SMD chips
- Constant current driver
- 60 degree gimble angle
- Adaptor plate is optional
- Fitting colour: White

INCLUDES

- Gimble LED downlight
- Non-dimmable driver
- 1.2 m flex and plug

APPLICATIONS

- Residential and hotels
- Conference rooms and reception areas
- Retail and commercial
- Aged care

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Cutout (mm)	Net Weight (kg)
173093	220-240V	38W	0.9	3000K	3800lm	60°	50000h	170	1.33
173094	220-240V	38W	0.9	4000K	4100lm	60°	50000h	170	1.33

Adaptor Plate (Optional)

Part No.	Cutout (mm)
292013	195

Part No.	Model No.	VEET Status	IPART Status
173093	YKRS6G1	Approved No.: 5477	Approved No.: 24143D15-KJIREFZ
173094	YKRS6G1	Approved No.: 5477	Approved No.: 24143D15-KJIREFZ

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C ~ +40 °C

