



## FEATURES

- Die-cast aluminium heat sink
- High efficiency SMD LED chips
- Opal polycarbonate diffuser
- IP54 weatherproof
- IC Rating. May be installed under ceiling insulation or against timber structure.

## DIMMING OPTIONS

- Trailing & Leading Edge.
- Universal

## INCLUDES

- Fixed head flush LED downlight
- Dimmable LED driver
- 1.2 m flex & plug

## APPLICATIONS

- Residential
- Hotels
- Shops
- Conference Rooms
- Reception areas

PRODUCT TESTING	IP CLASS	DIMMABLE	CERTIFICATION	DISTRIBUTION	DIMENSIONS(mm)

Part No.	Voltage [1] / Current(mA)	Watt./PF	Colour Temp.	Ra	Luminous Flux	Beam Angle	Lifetime L70B50	Dim	IP Rating	Housing Material	Fitting Colour
YKRS3S2F6-D-12W	220-240V/70	12W/0.9	3000K	≥80	920lm	90°	50,000h	YES	IP54	Die-casting Al	White
YKRS3S2F6-D-12W	220-240V/70	12W/0.9	4000K	≥80	990lm	90°	50,000h	YES	IP54	Die-casting Al	White
YKRS3S2F6-D-12W	220-240V/70	12W/0.9	3000K	≥80	920lm	90°	50,000h	YES	IP54	Die-casting Al	Satin Chrome
YKRS3S2F6-D-12W	220-240V/70	12W/0.9	4000K	≥80	990lm	90°	50,000h	YES	IP54	Die-casting Al	Satin Chrome

[1] Operating Frequency=50/60Hz

[2] Switch Times=20000

[3] This fitting is IP54 only once installed.