



Features

- Light weight construction
- Constant current driver
- UV resistant PC housing
- Corrosion resistant for seaside application
- Ingress Protection: IP65
- Impact Protection: IK08
- Easy to install

Includes

- 1.5m flex and plug

Installation Options

- Surface mounted installation

Applications

- Residential
- Light Commercial
- Light Industrial
- Gardens
- Parks
- Small Car Parks

Warranty

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING

Order Code	Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Size(L*W*H) mm	Net Weight (kg)
273135	273135	FLA6F 24W	220-240V	24W	0.9	5000K	2640lm	100°	50000h	187*197*43	0.52
273145	273145	FLA6F 45W	220-240V	45W	0.9	5000K	5000lm	100°	50000h	229*197*48	0.68
273155	273155	FLA6F 85W	220-240V	85W	0.9	5000K	10000lm	100°	50000h	326*297*62	1.58

[1] Operating Frequency = 50/60Hz;

[2] Operating Temperature: -30 °C ~ +50 °C

