energetic®
Smarter lighting

MarVelite Pro

Commercial / Industrial Floodlight

Features

- Die-cast aluminium body
- Built-in high efficiency SMD
- Tempered glass
- Ingress Protection: IP66
- Impact Protection: IK08
- High performance aluminium reflector
- Angle of support is adjustable up to 90°
- LED floodlight with driver

Includes

- 1.5m flex and plug

Applications

- Commercial
- Industrial
- Gardens
- Parks
- Car parks
- Sports centers

Warranty

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING
	IP66	Non-dim	Ra≥80		W H L	IK08 1.7kg at 300mm

Order Code	Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Lumen/W	Beam Angle	Lifetime L70B50	Size(L*W*H) mm	Net Weight (kg)
273164	273164	FLA7-H 90W	200-240V	90W	0.9	4000K	13300lm	150lm/W	110°	50000h	300*245*91	3.25
273165	273165	FLA7-H 90W	200-240V	90W	0.9	5000K	13300lm	150lm/W	110°	50000h	300*245*91	3.25
273174	273174	FLA7-H 120W	200-240V	120W	0.9	4000K	18200lm	150lm/W	110°	50000h	300*245*91	3.27
273175	273175	FLA7-H 120W	200-240V	120W	0.9	5000K	18200lm	150lm/W	110°	50000h	300*245*91	3.27
273184	273184	FLA7-H 165W	200-240V	165W	0.9	4000K	27000lm	165lm/W	110°	50000h	345*295*91	3.66
273185	273185	FLA7-H 165W	200-240V	165W	0.9	5000K	27000lm	165lm/W	110°	50000h	345*295*91	3.66

[1] Operating Frequency = 50/60Hz
[2] Operating Temperature: -30℃~+50℃

Floodlights

Specifications are for reference only and may be changed without prior notification.
Version: V1.0