



Features

- V Five-Colour selectable
- Multi-Watt selectable
- Large 6mm terminal block for easy installation
- High impact body and diffuser
- Stainless steel clips and screws
- Ingress Protection: IP65
- Impact Protection: IK08
- Side and rear cable entry options
- Flicker-Free driver

Includes

- Suspension brackets and cable gland

Installation Options

- Surface mounted
- Suspended (Suspension kit is required)

Applications

- Commercial
- Industrial
- Warehouses
- Car parks and garages
- Stations
- Food preparation areas

Warranty

- Five years for fitting

CERTIFICATION	IP RATING	FIVE-COLOUR	L70B50	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING

Order Code	Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Size(L*W*H) mm	Net Weight (kg)
211021	211021	WPB1-FC-N-2L60 20W	220-240V	10-20W	0.9	3000/4000/5000/5700/6500K	1000-2000lm	120°	655*115*86	1.28
211022	211022	WPB1-FC-N-2L120 40W	220-240V	10-40W	0.9	3000/4000/5000/5700/6500K	1000-4000lm	120°	1265*115*86	2.15

[1] Multi-Watt Selectable options:

- (2ft): 3-IN-1 20 / 14 / 10W
- (4ft): 8-IN-1 40 / 36 / 30 / 26 / 24 / 20 / 14 / 10W

[2] V Five-Colour Selectable options:

- 3K @ 93Lm/W
- 4K, 5K, 5.7K & 6.5K @ 100Lm/W

[3] Operating Frequency = 50/60Hz;

[4] Operating Temperature: -20 °C ~ +50 °C

