



Features

- V Five-colour selectable
- Multi-Watt selectable
- CRI: Ra>80
- High quality white powder coated sheet metal
- Wide 130mm body
- Smooth and highly transparent opal PC diffuser
- Large 6mm terminal block for easy installation
- Sustained emergency system
- Fully approved to AS2293 standards
- Flicker-Free driver

Includes

- Mounting accessories

Installation Options

- Surface mounted
- Suspended (suspension kit is required)

Applications

- Offices
- Garages
- Stations
- Industrial

Warranty

- Five years for fitting

Battens

CERTIFICATION	IP RATING	FIVE-COLOUR	L70B50	Ra	DISTRIBUTION	DIMENSIONS(mm)

Order Code	Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumen	Beam Angle	Size (L*W*H)mm	Net Weight (kg)
211025EM	211025EM	BTA3-FC-NEC-2L60 20W	220-240V	10-20W	0.9	3000/4000/5000/5700/6500K	1000-2000lm	120°	640*130*80	1.82
211026EM	211026EM	BTA3-FC-NEC-2L120 40W	220-240V	10-40W	0.9	3000/4000/5000/5700/6500K	1000-4000lm	120°	1240*130*80	2.95

[1] Multi-Watt Selectable options:

- (2ft): 3-IN-1 20 / 14 / 10W
- (4ft): 8-IN-1 40 / 36 / 30 / 26 / 24 / 20 / 14 / 10W

[2] V Five-Colour Selectable options:

- 3K @ 90Lm/W
- 4K, 5K, 5.7K & 6.5K @ 100Lm/W

[3] Operating Frequency = 50/60Hz;

[4] Operating Temperature: -20 °C ~ +50 °C

Emergency Performance

LUMINAIRE CLASSIFICATIONS	MAXIMUM SPACINGS(M)															
	MOUNTING HEIGHT (M)															
	2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	
C0-C180	D50	18.0	18.7	19.4	20.1	20.7	21.2	21.8	22.5	23.2	24.2	24.9	25.4	25.7	25.9	23.7
C90-C270	D32	15.4	16.1	16.7	17.2	17.6	18.0	18.5	19.1	19.5	20.2	20.6	20.7	20.6	20.3	14.6

Order Code of Battery	Part No. of Battery	Battery Capacity	Battery Voltage	Charging Time	Discharging Time	Battery Type
423019	423019	1500 mAh at 0.2 CmA	6.4V	7H	1.5H	LiFePO4

Specifications are for reference only and may be changed without prior notification.

