



Features

- Multi-Watt selectable
- High impact body and diffuser
- Large 6mm terminal block for easy installation
- Stainless steel clips and screws
- Ingress Protection: IP65
- Impact Protection: IK08
- Side and rear cable entry options
- Sustained emergency system
- Fully approved to AS2293 standards
- Stainless steel clips and screws
- Flicker-Free driver

Includes

- Suspension brackets and cable gland

Installation Options

- Surface mounted
- Suspended (Suspension kit is required)

Applications

- Commercial
- Industrial
- Warehouses
- Car parks and garages
- Stations
- Food preparation areas

Warranty

- Five years for fitting

Optional Accessories

- S316 stainless steel clips (232005)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING
						 IK08 1.7kg at 300mm

Order Code	Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Size(L*W*H) mm	Net Weight (kg)
213624EM	213624EM	WPB1-NEC-2L120 40W	220-240V	10-40W	0.9	4000K	1000-4000lm	120°	50000h	1265*115*86	2.15

[1] Multi-Watt Selectable options:

- 8-IN-1 40 / 36 / 30 / 26 / 24 / 20 / 14 / 10W

[2] Operating Frequency = 50/60Hz;

[3] Operating Temperature: -20 °C ~ +45 °C

S316 Stainless Steel Clips (Optional)

Order Code	Part No.	Model No.	Note
232005	232005	ECA01WP	S316 Stainless Steel Clips for Weatherproof Batten Tempest G3 and Tempest V range (10pcs/pack)

Emergency Performance

LUMINAIRE CLASSIFICATIONS		MAXIMUM SPACINGS(M)														
		MOUNTING HEIGHT (M)														
		2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15
C ₀ -C ₁₈₀	D63	19.4	20.3	21.1	21.8	22.4	23.0	23.7	24.5	25.2	26.4	27.4	28.1	28.6	28.9	28.0
C ₉₀ -C ₂₇₀	D32	15.4	16.1	16.7	17.2	17.6	18.0	18.5	19.1	19.5	20.2	20.6	20.7	20.6	20.3	14.6

Order Code of Battery	Part No. of Battery	Battery Capacity	Battery Voltage	Charging Time	Discharging Time	Battery Type
423019	423019	1500 mAh at 0.2 CmA	6.4V	7H	1.5H	LiFePO4

